



DIN 934 - UNI 5588 Hexagon Nuts

DIN 934 - UNI 5588 Sechskantmuttern


DIN 934 - UNI 5588 Écrous hexagonaux

DIN 934 - UNI 5588 Dadi esagonali

DIN 934 - UNI 5588 Tuercas hexagonales

Quality: I8I / 8 / 10 / 12

Coating Type: Zinc Plated / Hot Dip Galvanized / Geomet / Black Oxide



Size – D	Pitch (p)	E (Min.)	S (Min.)	S (Max.)	M (Min.)	M (Max.)	WEIGHT IN KG PER 1000 PCS
M8	1.25	14.4	12.7	13	6.4	6.8	5.2
M10	1.5	17.8	15.7	16	8	8.4	11.6
M12	1.75	20	17.7	18	10.4	10.8	17.3
M16	2	26.8	23.7	24	14.1	14.8	33.3
M18	2.5	29.6	26.2	27	15.1	15.8	49.4
M20	2.5	33	29.2	30	16.9	18	64.4
M22	2.5	37.3	33	34	18.1	19.4	79
M24	3	39.6	35	36	20.2	21.5	110
M27	3	45.2	40	41	22.5	23.8	165
M30	3.5	50.9	45	46	24.3	25.6	223
M33	3.5	55.4	49	50	27.4	26.7	288
M36	4	60.8	53.8	55	29.4	31	393
M39	4	66.4	58.8	60	31.8	33.4	502
M42	4.5	71.3	63.1	65	32.4	34	652
M45	4.5	77	68.1	70	34.4	36	800
M48	5	82.6	73.1	75	36.4	38	977
M52	5	88.3	78.1	80	40.4	42	1220
M56	5.5	93.6	82.8	85	43.4	45	1420
M60	5.5	99.2	87.8	90	46.4	48	1690
M64	6	104.9	92.8	95	49.1	51	1980